

# PRODUCT INFORMATION

## FLEXIBLE ACRYLIC FILLER

A high performance one part gunnable acrylic filler which can be used internally and externally for filling skirting boards, coving, window and door frames as well as sealing of internal fixtures, and repairing cracks and damage in walls and ceilings. The highly flexible nature of the product ensures the surface does not crack or de-bond on drying. Compatibility with most water based and synthetic paints greatly reduces the risk of surface cracking.

**NB: Some modern emulsion paints have a low pigment level and are therefore very prone to surface cracking. Always refer to the paint manufacturers' technical data sheets for advice on preparation.**

### PREPARATION

Surfaces should be dry, clean and free from dust, grease, loose or weakly adhered materials, water and other barriers to adhesion. The product will adhere to the majority of surfaces without the need to prime.

### APPLICATION

Do not apply at temperatures below 5°C. Good slump resistance and can be used in joints up to 20mm wide and 12mm deep.

1. Cut off the tip of the cartridge, leaving the thread intact. Screw on nozzle and cut at 45° to the required width.
2. Apply using a caulking gun to the area required. Ensure a good solid bead of DUNLOP FLEXIBLE ACRYLIC FILLER is achieved.
3. Smooth the DUNLOP ACRYLIC FILLER to the required finish.
4. Surrounding surfaces and tools can be cleaned using water.

### FINISHING

Paint and finishes can be applied once the surface is dry, this will take 1-2 hours depending on conditions.

### COVERAGE

1 x 310ml cartridge: -  
8.5m x 6mm x 6mm bead approx.

### STORAGE & SHELF LIFE

12 months in normal dry conditions. Store between 5° and 25°C. Protect from frost.

Please refer to the Material Safety Data Sheet for health and safety information.

Dunlop is a globally known brand name which is owned under licence by Building Adhesives Limited. Backed by the expertise of one of the most respected groups in the market for producing world class building and decorating products. The company prides itself on its reputation for offering solutions that combine technical quality with exceptional ease of use, along with the support of our team of technical experts with decades of experience in providing personalised solutions, whatever your problem.

To talk to us call: 01782 591100

Or visit our website: [www.dunlop-decorators.com](http://www.dunlop-decorators.com)

# PRODUCT INFORMATION

For free expert guidance on the use of this product or any aspect of ceramic tiling telephone the TECHNICAL ADVISORY SERVICE on: Tel: 01782 591120 Fax: 01782 591121.

**Note:** The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract tort, or otherwise) whatsoever for any loss, damage, or expense arising from the misuse of any information it supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or update information from time to time.