



CF-03

Grout from just

3 hours



FLEXIBLE, FAST SET FLOOR & WALL TILE ADHESIVE

A flexible, fast setting floor and wall tile adhesive for interior and exterior use. Ideal for fast track tiling, with the flexibility to cope with slight movement in substrates. Available in grey and white.



Sets in just 3 hours



Flexible



45 minute pot life



For internal and external use



One bag covers up to 5m² on floors or 10m² on wall areas



For your peace of mind

HOW TO FIX TILES IN WET AREAS:



For shower areas, always ensure the background is waterproof before tiling by using Dunlop Shower Waterproofing Kit.

Add one 20kg bag to 4.4 litres of cold, clean water, and mix to a smooth uniform consistency with an electric drill mixer. Allow to stand for 2 minutes, then re-mix for 30 seconds.

Within the 45 minute pot life, apply the adhesive onto the wall or floor and spread using a suitable notched trowel, with the ribs in one direction. Press the tiles firmly into the adhesive, checking periodically that good contact is maintained with the back of the tiles. Fix the tiles within 15-20 minutes of the adhesive being applied. Leave at least 2mm between wall tiles and 3mm between floor tiles for the grout joints.

Remove surplus adhesive from tiles and joints with a damp sponge/cloth and allow to fully set. Finish with Dunlop GX-500 Flexible Grout, available in 8 colours with a matching Dunlop FX-90 Sealant.

APPLICATION AREAS:

- ✓ Interior/external walls and floors
- ✓ Kitchens and bathrooms
- ✓ Power showers and wetrooms
- ✓ Swimming pools

TILE TYPES:

- ✓ Glazed and unglazed ceramic
- ✓ Porcelain
- ✓ Natural stone (non-translucent)
- ✓ Mosaics - ceramic, porcelain or natural stone
- ✓ Transparent or water sensitive natural stone (see product datasheet for details)

BACKGROUNDS:

- ✓ Concrete and cement/sand screeds
- ✓ Anhydrite screeds
- ✓ Plaster/plasterboard
- ✓ Existing unglazed tiles
- ✓ Fibre reinforced cement boards & tile backer boards
- ✓ Plywood overlay (min. 15mm thick)
- ✓ T&G floorboards
- ✓ Underfloor heated screed



Scan for product info datasheets, and videos.

Dunlop Sales: 01782 591160
Dunlop Technical: 01782 591120
info@dunloptrade.com
www.dunloptrade.com

Dunlop and the Flying D device are trademarks of Sumitomo Rubber Group and are used under license by Building Adhesives Ltd.