



### DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom.

No. DUN-004

1. Unique identification code of the product-type: **Dunlop Tile on Wood**
2. Intended use: **Dispersion adhesive for internal floor tiling.**
3. Manufacturer: **Building Adhesives Limited,  
Newstead Industrial Estate,  
Longton Road,  
Trentham,  
Stoke on Trent,  
Staffordshire,  
ST4 8JB**
4. Authorised representative: **Not applicable**
5. System or systems of AVCP: **System 3**
- 6a. Harmonised standard: **EN 12004:2007+A1:2012**


The Notified Body 1289 carried out the determination of the product type on the basis of type testing on samples taken by Building Adhesives Limited under System 3 and issued the test report (123455)-14018. Reaction to fire performance has been declared in accordance with the Commission Decision of 9<sup>th</sup> February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.

- 6b. European Assessment Document: **Not applicable**
7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007 +A1:2012
Bond strength as: - initial shear adhesion strength	$\geq 1.0\text{Nmm}^{-2}$	
Durability for; - shear adhesion strength after heat ageing	$\geq 1.0\text{Nmm}^{-2}$	
Release of dangerous substances	See SDS	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D

  
Stoke on Trent 29/11/22



UK CA 1289	
Building Adhesives Limited www.building-adhesives.com 22	
DUN 004 EN 12004:2007 +A1:2012 Dunlop Tile on Wood Dispersion adhesive for internal floor tiling	
Reaction to fire	Class E
Release of dangerous substances	See SDS
Bond strength, as: Initial shear adhesion strength	$\geq 1.0\text{Nmm}^{-2}$
Durability, for: Shear adhesion strength after heat ageing	$\geq 1.0\text{Nmm}^{-2}$