



CF-24

With an extended pot life of
5 hours

FLEXIBLE TILE ADHESIVE

Flexible standard setting floor and wall tile adhesive for porcelain and ceramics, with reduced slip and an outstanding pot life. Grout from 24 hours.



30 minute open time



Flexible



5 hour pot life



For internal and external use



One bag covers up to 5m² on floors or 10m² on wall areas



For your peace of mind

HOW TO INSTALL FLOOR & WALL TILES:



▶ Watch Now

MIX



Using an electric drill mixer (at under 300 rpm), mix 3 parts powder to 1 part cold, clean water by volume, or 5.6 litres of water per bag.

If it feels firm before the 5 hour pot life is up, you can remix, but don't add any more water.

APPLY



Spread the adhesive with a suitable notched trowel to cover approximately 1m², or an area that can be tiled within approximately 30 minutes. For floor tiling, large format wall tiles, wet areas and exterior situations, a solid-bed trowel must be used. Spread the adhesive so the ribs all go in one direction to help achieve a solid bed.

Press the tiles firmly into the adhesive, checking periodically that good contact is maintained with the back of the tiles. Leave at least 2mm between wall tiles and 3mm between floor tiles for the grout joints.

FINISH



Remove surplus adhesive from tiles and joints with a damp sponge/cloth and allow to fully set for 24 hours.

Finish with Dunlop GX-500 Flexible Grout, available in 8 colours with a matching Dunlop FX-90 Sealant.

APPLICATION AREAS:

- ✓ Interior/external walls and floors
- ✓ Kitchens and bathrooms
- ✓ Power showers and wetrooms
- ✓ Swimming pools or areas submerged in water

TILE TYPES:

- ✓ Glazed and unglazed ceramic
- ✓ Porcelain
- ✓ Mosaics - ceramic or porcelain

BACKGROUNDS:

- ✓ Concrete and cement/sand screeds
- ✓ Anhydrite screeds
- ✓ Plaster/plasterboard
- ✓ Existing unglazed tiles
- ✓ Fibre reinforced cement boards & tile backer boards
- ✓ Plywood overlay (min. 15mm thick)
- ✓ T&G floorboards
- ✓ Heated screed and undertile heating



Scan for product info, datasheets, and videos.

Dunlop Sales: 01782 591160
Dunlop Technical: 01782 591120
info@dunloptrade.com
www.dunloptrade.com



30 MINUTE OPEN TIME

Tiles can be fixed up to 30 minutes of DUNLOP CF-24 being applied, with a 20 minute adjustment period when the tiles are applied.



WATER RESISTANT

Suitable for areas continuously submerged in water such as swimming pools.



FROST RESISTANT

Suitable exterior areas such as patios.



DEPTH

Suitable for bed thickness from 2-6mm or up to 12mm in limited, isolated areas.



FLEXIBLE

Allows for small amounts of movement in the substrate, typically caused by changes in temperature or moisture.



CLASS C2TE

DUNLOP CF-24 exceeds the requirements of BS EN12004 for a C2TE tile adhesive.



UNDERFLOOR HEATING

Suitable for use over underfloor heated screeds and electric undertile heating. See datasheet for details.



SETTING TIME

DUNLOP CF-24 sets in 24 hours, after which, grouting can commence.



10 YEAR GUARANTEE

Guaranteed to be free from manufacturing defects and, when applied, to remain fit for the use for which they are specified by us for 10 years from the date of purchase.

