

# Product Selector



	READY MIXED ADHESIVES		POWDER ADHESIVES				GROUT	SEALANT
	RX-1000 Non Slip Wall Tile Adhesive	RX-3000 Waterproof Wall Tile Adhesive	CX-24 Essential Tile Adhesive	CF-24 Flexible Tile Adhesive	CF-03 Flexible Fast Set Tile Adhesive	CLF-03 Flexible Large Format & Natural Stone Adhesive	GX-500 Flexible Floor & Wall Grout	FX-90 Silicone Sealant
<b>CLASSIFICATION</b>	D1T	D2TE	C1T	C2TE	C2F	C2F	CG2WA	-
<b>COLOUR</b>	WHITE	WHITE	GREY / WHITE	GREY / WHITE	GREY / WHITE	GREY / WHITE	8 COLOURS – SEE WEBSITE	8 COLOURS – SEE WEBSITE
<b>SITUATION</b>	WALLS	WALLS	WALLS & FLOORS	WALLS & FLOORS	WALLS & FLOORS	FLOORS	WALLS & FLOORS	WALLS & FLOORS
Interior (dry)	●	●	●	●	●	●	●	●
Domestic showers	●	●	●	●	●	●	●	●
Power showers	-	●	●	●	●	●	●	●
Swimming pools	-	-	-	●	●	-	●	●
Exterior	-	-	●	●	●	●	●	-
Heated screeds	-	-	-	●	●	●	●	●
Undertile heating	-	-	-	●	●	●	●	●
<b>WALL BACKGROUNDS</b>								
Fibre / lightweight cement boards	●	●	-	●	●	-	●	●
Rendering	●	●	●	●	●	-	●	●
Existing glazed tiles	●	●	●	●	●	-	●	●
Existing unglazed tiles	●	●	●	●	●	-	●	●
Plaster	●	●	●	●	●	-	●	●
Plasterboard	●	●	●	●	●	-	●	●
<b>FLOOR BACKGROUND</b>								
Cement: sand screed	-	-	●	●	●	●	●	●
Concrete	-	-	●	●	●	●	●	●
T & G floorboards	-	-	-	●	●	●	●	●
Plywood overlay	-	-	●	●	●	●	●	●
Vinyl (not cushion) tiles	-	-	●	●	●	●	●	●
Mastic asphalt flooring grade	-	-	●	●	●	●	●	●
Fibre / lightweight cement boards	-	-	●	●	●	●	●	●
Existing glazed tiles	-	-	●	●	●	●	●	●
Existing unglazed tiles	-	-	●	●	●	●	●	●
Calcium sulphate / Anhydrite screeds	-	-	●	●	●	●	●	●
<b>TILE TYPE</b>								
Ceramic	●	●	●	●	●	●	●	●
Porcelain	-	-	●	●	●	●	●	●
Natural stone - translucent / water sensitive	-	-	-	-	●	●	●	-
Natural stone - non translucent	-	-	-	-	●	●	●	-
Mosaics - ceramic	●	●	●	●	●	●	●	●
Mosaics - porcelain	-	●	●	●	●	●	●	●
Mosaics - natural stone	-	-	-	-	●	●	●	-
<b>PROPERTIES</b>								
Setting time in hours (based at 20°C)	24 MINIMUM	24 MINIMUM	24	24	3	3	24	24
Bed thickness	3MM MAX.	3MM MAX.	3-6MM	3-6MM	3-6MM	3-25MM	-	6MM MAX. BEAD
Limited movement	-	●	●	●	●	●	●	●
Joint width	-	-	-	-	-	-	1-15MM	-

The above is a guideline only please refer to the information on the packaging and, for the latest information, the technical data sheet.

**Additional notes:** In shower areas and swimming pools a tanking system is recommended. Priming may be required on certain backgrounds. Consult the technical data sheet for further information. Always check the manufacturers instructions on heated floor systems, tiles and backer boards.



Contact our Technical Advisory Service on **01782 591 120**



Download product data sheets at **www.dunloptrade.com**