

# DUNLOP TEMPORARY TILE SEALER



## TECHNICAL SUMMARY

<b>Size</b>	500g
<b>Colour</b>	Clear
<b>Description</b>	Temporary protective sealer for use on most tile types to protect the surface of the tile from discolouration when grouting.
<b>Coverage</b>	500g undiluted covers approx. 5m <sup>2</sup> – on very porous backgrounds this may be less
<b>Setting Time*</b>	Allow 15 minutes minimum between coats
<b>Application Temperature</b>	Room Temperature approx. 20°C (do not use below 5°C)
<b>Storage &amp; Shelf Life</b>	Stored between 5°C and 30°C and protected from frost the shelf life of this product is 12 months.

\*depending on temperatures, background and site conditions

**TECHNICAL DATA – TEMPORARY TILE SEALER**

DATE ISSUED: 08.08.2023 Ref: DUN TTS/001

**TILE TYPE**

Glazed - ceramic	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Unglazed - ceramic	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Porcelain	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Natural Stone – translucent / water sensitive (water sensitive may suggest resin agglomerated stone)	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Natural Stone – non translucent	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Mosaics - ceramic	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Mosaics - porcelain	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.
Mosaics – natural stone	✓	Care must be taken not to get the DUNLOP TEMPORARY TILE SEALER in the grout joints. Use a cloth and apply just to the surface.

**For further advice or advice on any other situations not listed above, please contact DUNLOP TECHNICAL HELPLINE on 01782 591120**

**IN A NUTSHELL**

DUNLOP TEMPORARY TILE SEALER is a protective sealer for use on most tile types to protect the surface of the tile from discolouration during grouting. The sealer is removed by simply washing off after grout application.

**APPLICATION**

Ensure surface is clean and free from dust, apply undiluted sealer with a clean cloth before grouting avoiding the joints. Allow to dry for 15 minutes minimum before applying a second coat (more coats may be required depending on the material porosity) Allow to dry fully before commencing grouting. Note it must be applied and left to dry just before the grouting process.

**COVERAGE**

500g undiluted covers approx. 5m<sup>2</sup>, on very porous tiles this may be less.

**10 YEAR GUARANTEE**

As a testament to the reliability and performance of our rigorous quality control procedures, all Dunlop products carry a 10-year guarantee. Subject to terms and conditions -see website for details [www.dunloptrade.com](http://www.dunloptrade.com)

**HEALTH & SAFETY INFORMATION**

For detailed information on safety guidance, please refer to the Product Material Safety Data Sheet (available on request or via the Dunlop website [www.dunloptrade.com](http://www.dunloptrade.com))

**DUNLOP TECHNICAL HELPLINE**

For free expert guidance on the use of this product or any aspect of ceramic tiling telephone the DUNLOP TECHNICAL HELPLINE on 01782 591120 Fax: 01782 591121.

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract tort, or otherwise) whatsoever for any loss, damage, or expense arising from the misuse of any information it supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or update information from time to time.