



DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) 305/2011 (Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No. 574/2014 as it has effect in the United Kingdom.

No. DUN-003

1. Unique identification code of the product-type:
Dunlop Multi-Purpose Fix N Grout
2. Intended use:
Improved dispersion adhesive with reduced slip for internal wall tiling
3. Manufacturer:
**Building Adhesives Limited,
Newstead Industrial Estate,
Longton Road,
Trentham,
Stoke on Trent,
Staffordshire,
ST4 8JB**
4. Authorised representative:
Not applicable
5. System or systems of AVCP:
System 3
- 6a. Harmonised standard:
EN 12004:2007+A1:2012

The Notified Body 1289 carried out the determination of the product type on the basis of type testing on samples taken by Building Adhesives Limited under System 3 and issued the test report 604006726.

Reaction to fire performance has been declared in accordance with the Commission Decision of 9th February 2010 establishing the classes of reaction-to-fire performance for certain construction products as regards adhesives for ceramic tiles.

- 6b. European Assessment Document:
Not applicable

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 12004:2007 +A1:2012
Bond strength as: - initial shear adhesion strength	$\geq 1.0\text{Nmm}^{-2}$	
Durability for; - shear adhesion strength after heat ageing - shear adhesion strength at elevated temperature - shear adhesion strength after water immersion	$\geq 1.0\text{Nmm}^{-2}$ $\geq 1.0\text{Nmm}^{-2}$ $\geq 0.5\text{Nmm}^{-2}$	
Release of dangerous substances	See SDS	

8. The performance of the product identified above is in conformity with the set of declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: David Longwell – Head of R+D

Stoke on Trent 29/11/22



Building Adhesives Limited
www.building-adhesives.com
22

DUN 003
EN 12004:2007 +A1:2012
Dunlop Multi Purpose Fix N Grout
Improved dispersion adhesive with reduced slip
for internal wall tiling

Reaction to fire	Class E
Release of dangerous substances	See SDS
Bond strength, as: Initial shear adhesion strength	$\geq 1.0\text{Nmm}^{-2}$
Durability, for: Shear adhesion strength after heat ageing	$\geq 1.0\text{Nmm}^{-2}$
Shear adhesion strength at elevated temperature	$\geq 1.0\text{Nmm}^{-2}$
Shear adhesion strength after water immersion	$\geq 0.5\text{Nmm}^{-2}$