

Product Selector



<div><div><div></div><div>Suitable</div></div><div><div></div><div>Seek further advice by contacting the Dunlop Technical Helpline</div></div><div>Suitable when used with:</div><div><div><div></div><div>Dunlop Flexible Additive</div></div><div><div></div><div>Dunlop Tilers Primer / SBR Universal Bonding Agent</div></div><div><div></div><div>Dunlop SBR Universal Bonding Agent</div></div><div><div></div><div>Dunlop Procover</div></div></div></div>	READY MIXED ADHESIVES					POWDER ADHESIVES							GROUT	SEALANT
	RX-1000 Non Slip Wall Tile Adhesive	RX-2000 Showerproof Wall Tile Adhesive	RX-3000 Waterproof Wall Tile Adhesive	Multi Purpose Fix 'N' Grout	Tile-on-Wood	CX-24 Essential Tile Adhesive	CX-03 Fast Set Tile Adhesive	CF-24 Flexible Tile Adhesive	CF-03 Flexible Fast Set Tile Adhesive	CLF-03 Flexible Large Format & Natural Stone Adhesive	CS1-12 S1 Ultra Flexible Tile Adhesive	CS1-03 S1 Ultra Flexible Fast Set Tile Adhesive	GX-500 Flexible Floor & Wall Grout	FX-90 Silicone Sealant
CLASSIFICATION	D1T	D1TE	D2TE	D2T	–	C1T	C1F	C2TE	C2F	C2F	C2TES1	C2FS1	CG2WA	–
COLOUR	WHITE	BRILLIANT WHITE	WHITE	BRILLIANT WHITE	GREY / SANDSTONE	GREY / WHITE	GREY	GREY / WHITE	GREY / WHITE	GREY / WHITE	WHITE	WHITE	8 COLOURS - SEE WEBSITE	8 COLOURS - SEE WEBSITE
SITUATION	WALLS	WALLS	WALLS	WALLS	FLOORS	WALLS & FLOORS	WALLS & FLOORS	WALLS & FLOORS	WALLS & FLOORS	FLOORS	WALLS & FLOORS	WALLS & FLOORS	WALLS & FLOORS	WALLS & FLOORS
Interior (dry)														
Domestic showers														
Power showers	–	–		–										
Swimming pools	–	–	–	–	–	–	–			–				
Exterior	–	–	–	–	–									–
Heated screeds	–	–	–	–	–	–	–							
Undertile heating	–	–	–	–	–	–	–							
WALL BACKGROUNDS														
Fibre / lightweight cement boards					–	–	–			–				
Rendering					–					–				
Existing glazed tiles					–					–				
Existing unglazed tiles					–					–				
Plaster					–					–				
Plasterboard					–					–				
FLOOR BACKGROUND														
Cement: sand screed	–	–	–	–	–									
Concrete	–	–	–	–	–									
T & G floorboards	–	–	–	–		–	–							
Plywood overlay	–	–	–	–										
Vinyl (not cushion) tiles	–	–	–	–	–									
Mastic asphalt flooring grade	–	–	–	–	–									
Fibre / lightweight cement boards	–	–	–	–	–									
Existing glazed tiles	–	–	–	–	–									
Existing unglazed tiles	–	–	–	–	–									
Calcium sulphate / Anhydrite screeds	–	–	–	–	–									
TILE TYPE														
Ceramic														
Porcelain	–	–	–	–	–									
Natural stone - translucent / water sensitive	–	–	–	–	–	–		–			–			–
Natural stone - non translucent	–	–	–	–	–	–		–						–
Mosaics - ceramic														
Mosaics - porcelain	–	–		–	–									
Mosaics - natural stone	–	–	–	–	–	–		–						–
PROPERTIES														
Setting time in hours (based at 20°C)	24 MINIMUM	24 MINIMUM	24 MINIMUM	24 MINIMUM	24 MINIMUM	24	3	24	3	3	12-16	3	24	24
Bed thickness	3MM MAX.	3MM MAX.	3MM MAX.	3MM MAX.	3MM MAX.	3-6MM	3-6MM	3-6MM	3-6MM	3-25MM	2-6MM	2-6MM	–	6MM MAX. BEAD
Limited movement	–	–		–										
Joint width	–	–	–	–	–	–	–	–	–	–	–	–	1-15MM	–

The above is a guideline only please refer to the information on the packaging and, for the latest information, the technical data sheet.

Additional notes: In shower areas and swimming pools a tanking system is recommended. Priming may be required on certain backgrounds. Consult the technical data sheet for further information. Always check the manufacturers instructions on heated floor systems, tiles and backer boards.



Contact our Technical Advisory Service on **01782 591 120**



Download product data sheets at **www.dunloptrade.com**