



# GX-500

Smooth, durable and flexible floor & wall grout for joints up to 15mm



## FLEXIBLE FLOOR & WALL GROUT

DUNLOP GX-500 is a water-resistant, powder-based grout suitable for floors and walls. It's ideal for grouting ceramic, porcelain, and natural stone tiles indoors and outdoors. For the perfect finish, use Dunlop FX-90 Silicone Sealant in a matching colour.



Water resistant



Flexible



8 colours with matching silicones



For internal and external use




Available in 10kg and 2.5kg bags



For your peace of mind

### HOW TO GROUT TILES EASILY:



▶ Watch Now

#### PREPARE



Make sure the tile adhesive is completely dry before grouting. If a ready mixed adhesive has been used on surfaces with low porosity, wait 3 days before grouting. Clean and dry the joints before grouting, removing any debris. Avoid grouting below 5°C or in damp conditions.

#### MIX



Add 3.5 parts powder to 1 part cold water by volume, and mix to a smooth paste, wait for 2-3 minutes and mix briefly again. Aim to mix enough for a 45 minute working time at 20°C. For demanding areas, such as single layer timber floors, or power showers with body jets, mix with **Dunlop Flexible Additive** pre-diluted 1:2 by volume with water.

Note: A 2.5kg bag will cover approximately 6.5m<sup>2</sup> and a 10kg bag will cover approximately 26m<sup>2</sup> based on a 3mm joint and 300mm x 300mm x 7mm tiles.

#### APPLY



Fill tile joints using a squeegee or grout float. Compact and remove excess grout as you go. Let grout dry for 15 minutes, then damp-sponge off the excess working diagonally across the joints. Polish the tiles with a dry clean cloth once grout has sufficiently set.

Tiles can handle normal conditions after 24 hours. For external areas, shield from weather and frost during application and 24 hours after grouting. Showers shouldn't be used for 2 weeks after grouting, in accordance to British Standards BS 5385.

#### CLASSIFICATION:



**CG2:** Cementitious grout with improved performance

**W:** Improved water resistance

**A:** Improved abrasion resistance

#### APPLICATION AREAS:

- ✓ Interior/external floors and walls
- ✓ Kitchens, bathrooms, showers
- ✓ Power showers
- ✓ Swimming pools
- ✓ Underfloor heated screeds
- ✓ Electric undertile heated floors

#### TILE TYPES:

- ✓ Glazed and unglazed ceramic
- ✓ Porcelain
- ✓ Brick slips
- ✓ Mosaics - ceramic, porcelain or natural stone
- ✓ Natural stone (see product datasheet for details)



Scan for product info datasheets, and videos.

Dunlop Sales: 01782 591160

Dunlop Technical: 01782 591120

info@dunloptrade.com

www.dunloptrade.com

Dunlop and the Flying D device are trademarks of Sumitomo Rubber Group and are used under license by Building Adhesives Ltd.



# 2 STEPS TO PERFECTION

**The go-to products for the perfect finish.**

Available in 8 different colours, our matching grout and silicone sealants help you produce a professional finish to your tiling jobs, every time.

MIST GREY

LIQUORICE BLACK

GRAPHITE GREY

JASMINE CREAM

POLAR WHITE

CONKER BROWN

HARVEST BEIGE

SAHARA SAND

## JOB DUN RIGHT